



- Electronic Intensity Stabilizer ensures consistent performance.
   Beam strength will not weaken between charges!
- · Instant-on operation; lamp reaches full power immediately
- Portable and rugged. Anodized aluminum lamp body minimizes corrosion and stands up to years of heavy use.
- Powered by a rechargeable NiMH battery. Provides 90 minutes of continuous inspection between charges.

MODEL	NOMINAL STEADY-STATE UV-A INTENSITY at 15 in (38 cm) <b>①</b>	<b>UV-A COVERAGE AREA</b> at 15 in (38 cm) at minimum 1,200 μW/cm²	VISIBLE LIGHT MEASUREMENT
OPX-365	18,000 μW/cm <sup>2</sup>	2.5 in (6.3 cm) Diameter	<2 foot-candles (22 lux)

**Light Source:** UV-A (365 nm) Lamp Style: Cordless flashlight Lamp Head Diameter: 2 in (5.1 cm) Length: 8 in (20.3 cm) Weight: 11.8 oz (335 g) (with Battery) 3.6V, 2.0 Ah NiMH internal Power Requirements: battery stick (rechargeable) Run Time: 90 minutes (continuous) **Charge Time:** 4 hours

⊕ UV-A intensity reading taken with the Spectroline® AccuMAX™
Series meter, and is factory set to the value shown.







Comes complete with OPTIMAX™ 365 (365 nm) lamp, smart AC and DC chargers, UV-absorbing spectacles, belt holder and hard carrying case. AC charger available in 120V, 230V, 240V or 100V versions.






## **UV-A** Beam Profiles







**DISTRIBUTED BY:**